

Approval Date: 20 May 1998

Reviewed on : 23 October 2007

Version: 1

## Purpose

The boat trailer will be used to transport the survey boats to and from measuring sites.

## Conditions & Requirements

- The boat trailer shall be of such a design, that the boat can be transported reliably and safely by road, to very remote sites.
- The trailer shall be easy to use and maintain.
- The trailer shall be supplied with the accessories as needed for effective use.
- The trailer shall be supplied with a spare wheel with tyre, securely fixed at an easily accessible spot.
- The trailer shall have an expected technical lifetime of not less than 10 years.
- The trailer shall be very sturdy.
- The trailer shall have adequate and strong provisions to secure the boat.
- The trailer shall have ample and large supports fitting the shape of the boat's hull
- The trailer shall be fitted with a safety chain to attach it to the pulling car.

## Specifications

### 1. Trailer

<b>material</b>	galvanised iron
<b>capacity</b>	maximum 1000 kg
<b>length</b>	matching the size of the boat

### 2. Trailer outfit

<b>winch</b>	with ratchet and pawl for pulling the boat onto the trailer
<b>guidance rollers</b>	rubber, fitting to the shape of the boat
<b>lights</b>	removable assembly of taillights
<b>spare tyre</b>	spare wheel with tyre

**Approval Date: 20 May 1998****Version: 1****Purpose**

The boat trailer will be used to transport the survey boats to and from measuring sites.

**Conditions & Requirements**

- The boat trailer shall be of such a design, that the boat can be transported reliably and safely by road, to very remote sites.
- The trailer shall be easy to use and maintain.
- The trailer shall be supplied with the accessories as needed for effective use.
- The trailer shall be supplied with a spare wheel with tyre, securely fixed at an easily accessible spot.
- The trailer shall have an expected technical lifetime of not less than 10 years.
- The trailer shall be very sturdy.
- The trailer shall have adequate and strong provisions to secure the boat.
- The trailer shall have ample and large supports fitting the shape of the boat's hull
- The trailer shall be fitted with a safety chain to attach it to the pulling car.

**Specifications****3. Trailer**

<b>material</b>	galvanised iron
<b>capacity</b>	maximum 1000 kg
<b>length</b>	matching the size of the boat

**4. Trailer outfit**

<b>winch</b>	with ratchet and pawl for pulling the boat onto the trailer
<b>guidance rollers</b>	rubber, fitting to the shape of the boat
<b>lights</b>	removable assembly of taillights
<b>spare tyre</b>	spare wheel with tyre